



UPC-GBV-429

CAST STEEL GLOBE STEAM STOP VALVE CLASS-300#

Design Features:

- UPC Cast Steel (A 216 Gr. WCB) Globe Valve.
- Renewable Seat
- Bolted Bonnet
- Outside Screw and Yoke Type
- Raised Face Drilled/ Undrilled

Conformity to Standard & Codes:

- Product Standard-BS 1873 Class-300#
- Testing Standard-API-598
- End Details-Flanged Ends to BS: 1560 / ANSI-B 16.5, Class-300#, Raised Face Drilled/Undrilled.

Design Features

- Stream Line shaped flow way area for smooth flow of working fluid for minimum pressure drop.
- Bolted Body Bonnet Joint.
- Renewable Body Seat & Disc Facing Rings.
- Bolted Gland.
- Back seating arrangement permits the replacement of gland packing in fully open position while the Valve is under inline pressure.
- Large lift to avoid obstruction in the flow way area.
- Sturdy spoked handwheel clear from the top of yoke is provided for operation of the Valve.
- Designed for tight shut off & efficient fluid flow control.
- Ample depth of stuffing Box.

Applications

- Steam Industries
- Water Supply & Solvent Industries
- Oil Industries
- Process Industries

Water Steam Oil Air

Test Certificate in Form III_C as per IBR is Furnished with every supply

UPC INSTRUMENTS PVT.LTD.
AN ISO 9001:2015, 14001-2015 CE & TÜV SÜD CERTIFIED COMPANY



CAST STEEL GLOBE VALVE 300#



DIMENSIONS:

NOMINAL SIZE												
Inches	Size in mm	FF ±2	ØFD	ØW	ØRFD	ØRFH	k	n	Ød	FT	H	
1"	25	203	124	160	51	2	89	4	19	17	280	
1 1/4"	32	216	133	160	63	2	99	4	19	19	280	
1 1/2"	40	229	155	200	73	2	114	4	19	20.6	310	
2"	50	267	165	200	92.10	2	127	8	19	22.7	325	
2 1/2"	65	292	190	250	105	2	149	8	22.4	26	380	
3"	80	318	210	250	127	2	168.3	8	22.4	29	430	
4"	100	356	255	300	157	2	200	8	22.4	32.2	510	
5"	125	400	280	350	188	2	235	8	22.4	33.4	600	
6"	150	444	320	450	216	2	270	12	22.4	37	590	
8"	200	559	380	500	270	2	330.2	12	25.4	41.70	670	
10"	250	622	444.5	560	334	2	387.4	16	28.4	48	725	
11"	300	711	521	610	381	2	450.90	16	31.80	51	800	



*All dimensions are in mm unless and otherwise specified.

PART LIST


S NO	PART NAME	MATERIAL	STANDARD
1.	Body	C.S.	A 216 Gr. WCB
2.	Body Seat Ring	SS	ASTM A276 TYPE 304
3.	Plug	SS	ASTM A276 TYPE 410
4.	Plug Nut	SS	ASTM A276 TYPE 410
5.	Spindle	SS	ASTM A276 TYPE 410
6.	Back seat (BB)	SS	ASTM A276 TYPE 410
7.	Gasket	Graphite	SPW SS + Graphite
8.	Bonnet	C.S.	A 276 Gr. WCB
9.	Joint Studs & Nuts	SS	A193 Gr. B7 & A 194 Gr. 2H
10.	Cross Studs & Nuts	SS	A193 Gr. B7 & A 194 Gr. 2H
11.	Gland packing	Graphite	Graphite Ring
12.	Gland bush	SS410	A 276 TP 410
13.	Gland flange	SS	A 276 Gr. WCB
14.	Eye Bolts & Nuts	C.S.	A193 Gr. B7 & A 194 Gr. 2H
15.	Yoke Sleeve	C.S.	A193 Gr. B7 & A 194 Gr. 2H
16.	Hand Wheel	C.S.	A193 Gr. B7 & A 194 Gr. 2H
17.	Hand Wheel Nut	SS	S.S
18.	Hand wheel washer	SS	S.S

WARRANTY

All the valves are warranted against any manufacturing defect for a period of 12 months from date of supply, provided the valves has not been misused, damaged, installed for services it is not recommended or the seal has been tampered with. The company shall be liable to furnish part/ parts thereof or full Valve as the company may deem fit.

TEST PRESSURE:

TYPE OF TEST	Maximum Pressure at 400°C
Body	76.6 Kg/cm ²
Seat	56.4 Kg/cm ²
Back Seat	56.1 Kg/cm ²



UPC INSTRUMENTS PVT.LTD.
AN ISO 9001:2015, 14001-2015 CE & TÜV SÜD CERTIFIED COMPANY



Office: Plot No. 18, Towel Market, Gohana Road, Panipat-132103 (HARYANA)

Manufacturing Unit: Plot no.125,Near Tehsil, Dinger Majra Road, Gharaunda, Karnal-132114 (HARYANA)

✉ : info@unitechmeter.com ✉ : ho@unitechmeter.com ✎ : www.unitechmeter.com